



Note: See last page of DLVM section for drawing of low headroom EDL under running style.

DL	E min	E1	LA	M6	M7	N min	RF	T
4	3.25	0.88	18	8.5	6.38	8	7.38	0.88

Max. U1/U2 = 20"

## Single Girder Under Running Crane Type DLVM2

Cap. Tons	Hoist			Trolley			Endtruck			Bridge						Corner Load F Lbs.	Shipping Weight Lbs.																	
	Type Reeving Rope Dia.	Speed FPM HP	Lift Ft.	Type Weight	HP per Motor 65/16 FPM	Wheel		Length Ft.-In.	HP per Motor 120/30 FPM	Span Ft.	U1/U2	L1 In.	L2 In.	A1 In.	C1 In.			K1 In.																
						Dia. In.	Base Ft.-In.																											
2	820 4/1 0.25	16/2.6 .4/.059	20	EM832L6 163.41.060 620 lbs.	.29/.07	4	5'-0"	6'-3"	2x0.33	24	20	12	-2	20	36	8	2815	3120																
																	28	2900	3420															
																	32	2995	3920															
																	36	3130	4220															
																	40	3325	4720															
																	44	3460	5280															
																	48	3670	7070															
																	52	3900	7520															
																	56	4271	8094															
																	60	4550	9116															
																							6'-6"	7'-9"										
																							7'-6"	8'-9"										