

EMH Wire Rope Hoists

Dimensions and Specifications

Hoist Model: EM 3000E
Trolley Type: Monorail for Single Girder Cranes

Reeving: 2 to 1

Capacities: 7 tons

Rope Diameter (mm):	13
Drum Diameter:	10.75"
Sheave Diameter:	9.125"
Hoist Motor HP:	15.5/2.6
Trolley Motor HP:	2x0.6/0.15
Trolley Wheel Diameter:	6.25"
Speeds (fpm)	32/5.2, 50/8.2
Trolley Speed (fpm):	65VFD

Duty Service Classification		FEM	HMI
Capacity in US Tons	7	1	H3

Dimensions (inches):		
Refer to drawing below. C, M and R dimensions shown in adjacent tables.	A:	23.25
	B:	24
	G:	15.125
	H:	10.5
	I:	6.25
	K:	5.375
	L:	15.75
	N-Min:	5
N-Max:	20	
Maximum Flange Thickness:	1.535	

Available Lifts (ft):				
M, R and Wt. vary with lift		M (in.)	R (in.)	Wt. (lbs.)
	40	8.125	37.125	2650
	65	13.375	47.5	2875
	100	20.25	60.75	3325

C Dimension - inches:			
Varies with flange width (N)	N<12"	12"<N<16"	N>16"
	28.625	30.625	35.25

