

# EMH Wire Rope Hoists

## Dimensions and Specifications

**Hoist Model: EM 3000D**  
**Trolley Type: Top Running for Double Girder Cranes**

**Reeving: 8 to 2**

**Capacities: 7.5 and 10 tons**

<b>Rope Diameter:</b>	2x8 mm
<b>Drum Diameter:</b>	10.625"
<b>Sheave Diameter:</b>	9.125"
<b>Hoist Motor HP:</b>	12.4/2
<b>Trolley Motor HP:</b>	2 x 0.5
<b>Speeds (fpm):</b>	16/2.6
<b>Std. Trolley Speed (fpm):</b>	80 VFD

<b>Duty Service Classification</b>		<b>FEM</b>	<b>HMI</b>
<b>Capacity in US Tons</b>	<b>7.5</b>	3	H5
	<b>10</b>	2	H4

<b>Dimensions (inches):</b>	
<b>B:</b>	28
<b>C:</b>	17
<b>DA:</b>	5.125
<b>DL:</b>	6.125
<b>E:</b>	2.5
<b>F:</b>	2.25
<b>G:</b>	4
<b>H:</b>	23
<b>K:</b>	4
<b>O *:</b>	16.5
<b>P:</b>	3.125
<b>R:</b>	42
<b>U *:</b>	10.25
<b>X:</b>	0.625

Refer to drawing below. M, T and Standard SP (trolley gauge) dimensions plus weight shown in adjacent tables.

<b>Standard SP (trolley gauge):</b>				
<b>Varies with lifts shown at right.</b>	<b>5 ft.</b>	<b>13 ft.</b>	<b>22 ft.</b>	<b>33 ft.</b>
		63	78.75	98.5

<b>Available Lifts (feet):</b>				
<b>M, T, and Wt. vary with lift.</b>		<b>M (in.)</b>	<b>T (in.)</b>	<b>Wt. (lbs.)</b>
	<b>5</b>	0	30	2200
	<b>13</b>	0	32	2250
	<b>22</b>	0	35	2300
	<b>33</b>	0	43	2350

\* Dimensions O and U may vary depending on the type of control.

